

**Amendments to the Claims:**

Status of Claims:

Claims 1, 5-7, 11-13, 17-21, and 25-30 are pending for examination.

Claims 1, 7, 13, and 19 are in independent form.

Claims 1, 5-6, 7, 11-12, and 17-18 are amended herein.

1. (Currently Amended) A method for measuring the performance of a scalable network comprising:

preparing a network under test for testing;

establishing a static Internet Protocol (IP) routing path for a session to be tested ~~wherein said routing path is a static IP route;~~

sending, by a packet generator at a first end of the static IP routing path said ~~Static IP route~~, a constant stream of packets through the a network under test;

counting, a number of packets received by a packet count unit at a second end of the static IP routing path, ~~received packets at the packet count unit at a second end of said static IP route;~~ and

establishing a peak performance rate as the highest rate at which packets can be sent from the packet generator to the packet count unit with no packet dropout.

2-4. (Cancelled)

5. (Currently Amended) The method of claim 1, where ~~wherein said act of~~ sending a constant stream of packets includes ~~the act of sending said~~ sending a constant stream of packets over an OC-3 level network.

6. (Currently Amended) The method of claim 1, where ~~wherein said act of~~ sending a constant stream of packets includes ~~the act of sending~~ the said constant stream of packets over an OC-12 level network.

7. (Currently Amended) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method for measuring the performance of a scalable network, said method comprising:

~~preparing the scalable network for testing;~~

establishing a static Internet Protocol routing path between a packet sender and a packet receiver for a session to be tested ~~wherein said routing path is a static IP route a server at a first end of said route and a client node at a second end of said route;~~

sending, by the packet sender ~~a server~~, a constant stream of packets to the packet receiver ~~a client node~~;

counting, at the packet receiver ~~by said client node~~, the number of packets received at the packet receiver ~~said packets received at said client node~~, where the counting is performed without examining the contents of a received packet; and

establishing a peak performance rate as the highest rate at which packets are received at the packet receiver with no packet dropout.

8-10. (Cancelled)

11. (Currently Amended) The program storage device of claim 7, where ~~wherein~~ ~~said act of sending a constant stream of packets includes the act of sending the~~ said constant stream of packets over an OC-3 level network.

12. (Currently Amended) The program storage device of claim 7, where ~~wherein~~ ~~said act of sending a constant stream of packets includes the act of sending the~~ said constant stream of packets over an OC-12 level network.

13. (Previously Presented) An apparatus for measuring the performance of a scalable network comprising:

means for preparing the network for testing;

means for establishing a routing path for a session to be tested wherein said routing path is a static IP route having a server at a first end of said route and a client node at a second end of said route;

means in a server for sending a constant stream of packets to a client node;

means in said client node for counting said packets received by said client node; and

means for establishing a peak performance rate as the highest rate with no packet dropout.

14-16. (Cancelled)

17. (Currently Amended) The method of claim 13, where the means for sending a constant stream of packets includes means for ~~the act of sending the~~ said constant stream of packets over an OC-3 level network.

18. (Currently Amended) The method of claim 13, where the means for sending a constant stream of packets includes means for ~~the act of sending the~~ said constant stream of packets over an OC-12 level network.

19. (Previously Presented) A system for measuring the performance of a scalable network comprising:

a packet generator in a source node at a first end of a static IP route for providing test packets to a network under test;

a packet count unit in a client node at a second end of said static IP route for counting test packets received by said client node from said network under test;  
and

wherein said test packets are provided in a constant stream to said network under test and wherein a peak performance rate of said network under test is established as the maximum receive rate at a particular packet size with no packet dropout.

20. (Original)        The system of claim 19, wherein said network under test comprises a OC-3 level network.

21. (Original)        The system of claim 19, wherein said network under test comprises a OC-12 level network.

22-24. (Cancelled)

25. (Original)        The system of claim 20, wherein said network under test includes two Fast Ethernet pathways.

26. (Original)        The system of claim 21, wherein said network under test includes eight Fast Ethernet pathways.

27. (Original)        The system of claim 21, wherein said network under test includes at least two Gigabit Ethernet pathways.

28. (Original)        The system of claim 21, wherein said network under test includes four OC-3 pathways.

29. (Original)        The system of claim 19, wherein said packet generator is configured using Pagent software.

30. (Original)        The system of claim 19, wherein said system is configured to download a test configuration file from a TFTP server.